


Modular Belt Conveyors / Elevators



Anglia Autoflow's **Plastic Belt Conveyors / Elevators** are reliably transporting a wide range of products in many different industries around the world.



Food Applications

Open hinge design belt and 'easy-clean' conveyor construction allowing a high level of hygiene to be maintained. Stainless steel and food grade plastic are used throughout, all finished to a very high standard.

Packaged Goods

Belt materials with good impact resistance combined with heavy duty conveyor construction provide reliability and durability in extreme conditions.

Tel: +44 (0) 1379 651031
 Fax: +44 (0) 1379 652832
 Email: sales@aaflow.com
 Web: www.aaflow.com



Belt Width (mm)	Mean Radius (mm)
200	540
300	810
500	1350
600	1620

STANDARD RANGE (others available on request)											
Belt Widths (mm)	200				300				500 or 600		
Belt Type	Straight		Sideflexing		Straight		Sideflexing		Straight		Sideflexing
Transfer Diameters (mm)	100	165	100	130	100	165	100	130	165	100	130
Belt Speeds (m/min)	11 or 15	19 or 24	11 or 15	15 or 19	11 or 15	19 or 24	11 or 15	15 or 19	19 or 25	11 or 15	15 or 19
Belt Material	White or Blue polypropylene, polyethylene, acetal, or nylon										

